### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

### (19) World Intellectual Property Organization International Bureau



### 

### (43) International Publication Date 9 December 2004 (09.12.2004)

### (10) International Publication Number WO 2004/105546 A2

(51) International Patent Classification7:

**A46B** 

(21) International Application Number:

PCT/IB2004/001887

(22) International Filing Date:

2 June 2004 (02.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/474,910

2 June 2003 (02.06.2003) US

(71) Applicant (for all designated States except US): SPRING-BOOST S.A. [CH/CH]; Chemin de la Dauphine 9, CH-1291 Commugny (CH).


(72) Inventors; and

- (75) Inventors/Applicants (for US only): FUCHSLOCHER, Jörg [DE/CH]; 33, route de Bramblens, CH-1027 Lonay (CH). BEHROUZ, Bayat [IR/CH]; Ave. du Servan 25, CH-1006 Lausanne (CH).
- (74) Agent: MOETTELI, John; Moetteli & Associés, Case

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AÙ, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EB, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

### Declarations under Rule 4.17:

as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(il)) for the following designations AE,



than the thickness of the heel portion, thereby defining a characteristic angle of declination from the forefoot region to the heel portion. The constraining device substantially constrains a wearer's metatarsal-phalangeal joints from movement when exercising. The forefoot region has a curved form defined so as to further minimize flexion of the metatarsalphalangeal joint.

# (19) World Intellectual Property Organization

International Bureau



## A CORNE BUILDING DE THE HEAR BEING BEING BUILD AND HEAR HARD BUILD BUILD BUILD BUILD BUILD BUILD BUILD BUILD BUILD

(43) International Publication Date 9 December 2004 (09.12.2004)

PCT

# (10) International Publication Number WO 2004/105546 A3

(51) International Patent Classification<sup>7</sup>: 7/22, 7/14, 17/02, 21/26, 13/18

A43B 13/14,

(21) International Application Number:

PCT/IB2004/001887

(22) International Filing Date:

2 June 2004 (02.06.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/474,910

2 June 2003 (02.06.2003) US

- (71) Applicant (for all designated States except US): SPRING-BOOST S.A. [CH/CH]; Chemin de la Dauphine 9, CH-1291 Commugny (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): FUCHSLOCHER, Joerg [DE/CH]; Springboost S.A., EPFL PSE-A, CH-1015 Lausanne (CH). BEHROUZ, Bayat [IR/CH]; Ave. du Servan 25, CH-1006 Lausanne (CH).
- (74) Agent: MOETTELI, John; Moetteli & Associés SARL, St Leonhardstrasse 4, CH-9000 St. Gallen (CH).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

### Declarations under Rule 4.17:

 as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,

[Continued on next page]

(54) Title: IMPROVED DORSIFLEXION SHOE



(57) Abstract: A high performance dorsiflexion shoe (10) has a sole and a constraining device (16) above the metatarsal-phalangeal joint. The sole has a ground-contacting surface (26), a forefoot region (30), a midfoot region (32) and a heel portion (34). The forefoot region (30) is made of a high density material, and has a thickness (T), measured in a direction perpendicular to the ground-contacting surface (26) of the sole, greater than the thickness (t) of the heel portion, thereby defining a characteristic angle (a) of declination from the forefoot region (30) to the heel portion (34). The constraining device (16) substantially constrains a wearer's metatarsal-phalangeal joints (20) from movement when exercising. The forefoot region has a curved form (28) defined so as to further minimize flexion of the metatarsalphalangeal joint (20).



CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM,

ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

of inventorship (Rule 4.17(iv)) for US only

#### Published:

- with international search report
- with amended claims

## (88) Date of publication of the international search report: 31 March 2005

Date of publication of the amended claims: 27 October 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/105546 PCT/IB2004/001887

### AMENDED CLAIMS

[received by the International Bureau on 02 February 2005 (02.02.05); original claims 1 and 2 amended; remaining claims unchanged (1 page)]

- 1. A high performance dorsiflexion shoe for enveloping a foot (40) of a wearer, including the wearer's metatarsal-phalangeal joint (20), the shoe comprising
- (a) a sole portion (24) having a ground-contacting surface (26), a forefoot region (30), a midfoot region (32) and a heel portion (34), and
  - (b) a constraining device (16) above the metatarsal-phalangeal joint;

wherein the forefoot region is made of a high density material, and has a thickness, measured in a direction perpendicular to the ground-contacting surface of the sole portion, greater than the thickness of the heel portion, thereby defining a dorsiflexion shoe having a characteristic angle ( $\alpha$ ) of declination from the forefoot region to the heel portion;

wherein the constraining device substantially constrains a wearer's metatarsal-phalangeal joints from movement when exercising,

wherein the forefoot region has a curved form defined so as to further minimize flexion of the metatarsal-phalangeal joint during walking or running and

wherein the sole portion (24) is a component of a shell (12) which includes sidewall portions (22) extending upwardly from the sole portion.

- 2. The shoe of claim 1, wherein the sidewall portions (22) extend upwardly from the sole portion to a circumferential edge (13) which surrounds the wearer's foot (40).
- 3. The shoe of claim 2, wherein the circumferential edge (13) is higher in the heel region (34) than in the forefoot region (30), thus giving the outward appearance of a plantarflex shoe.
- 4. The shoe of claim 1, wherein the forefoot region (30) includes at least one hard, high density insert (66, 162, 180, 182, 184, 186, 190) formed to follow the curvature of the sole portion (24).
- The shoe of claim 4, wherein the at least one insert (66, 162, 180, 182, 184, 186, 190) includes reinforcing ribs (90).